


M1 – 4-digit digital panel meter in 96x48 mm (BxH) Pt100 2-/3-wire -200°C...850°C / -328°F...1562°F

- red display of -1999...9999 digits (optional green, orange or blue display)
- minimal installation depth: 25 mm without plug-in terminal
- adjustment via factory default or directly on the sensor signal
- min/max-value recording
- displayed in °C or °F
- display flashing at threshold exceedance / undershooting
- navigation keys for the recall of min/max-values or limit value corrections during operation
- impedance matching
- programming interlock via access code
- protection class IP65 at the front
- plug-in terminal
- accessories: pc-based configuration-kit PM-TOOL with USB adapter
- on request: devices for working temperatures of -40°C...+70°C



ORDER NUMBER **EUR**
(without options)

• Pt100 2-/3-wire -200°C...850°C / -328°F...1562°F



Supply 230 VAC

M1-1TR4B.030C.570xD **162.00**

Supply 24 VDC

M1-1TR4B.030C.770xD **174.70**

• Product key options

M	1-	1	T	R	4	B.	0	3	0	C.	5	7	0	x	D	EUR		
M	1-	1	T	R	4	B.	0	3	0	C.	7	7	0	x	D			
																D	Dimension/physical unit, customer-specific settings	20.00
																1	Without keypad, operation via PC software PM-TOOL	10.60
																X	Other voltage supplies on request!	
																B	Blue	35.00
																G	Green	10.10
																Y	Orange	10.10

Please state physical unit in order, e.g. °F.

• Parameterisation software

PC based configuration software PM-Tool for devices without keypad, for a simple adjustment of standard devices, incl. USB-adapter. Programming happens via an interface on the back.

PM-TOOL-MUSB4 **94.30**

• Technical data

Dimension	Housing	B96xH48xD25 mm (including plug-in terminal D= 38 mm)
	Panel cut-out	92.0 ^{+0.8} x 45.0 ^{+0.6} mm
	Fixing	screw elements for insulation thickness up to 3 mm
	Housing material	PC Polycarbonate, black
	Sealing material	EPDM, 65 Shore, black
	Protection class	at the front IP65 standard, back side IP00
	Weight	approx. 100 g
Display	Connection	plug-in terminal; line cross-section up to 2.5 mm ²
	Display	4-digit
	Digit height	14 mm
	Segment colour	red (standard), optional available in green, blue and orange
	Display range	-1999 to 9999
	Setpoints	optical display flashing
	Overflow	horizontal bars at the top
Measuring input	Underflow	horizontal bars at the bottom
	Display time/ Measuring time	0.1 to 10.0 seconds
	Span	-200°C...850°C / -328°F...1562°F
	Measuring fault	0.1% of measuring range, ± 1 digit
	Temperature drift	100 ppm/K
	Measuring time	0.1 ... 10.0 seconds
	Measuring principle	U/F-conversion
Power pack	Resolution	approx. 0.1°C or 0.1°F
	Supply	230 VAC ±10% (max. 3 VA) 24 VDC ±10%, galvanic isolated (max. 1 VA)
Memory	EEPROM	Data life ≥ 100 years at 25°C
Ambient conditions	Working temperature	0 to +60°C
	Storing temperature	-20 to +80°C
	Climatic density	relative humidity 0-85% on years average without dew
CE-sign	Conformity to directive 2014/30/EU	
EMV	EN 61326, EN 55011	
Safety standard	According to low voltage directive 2014/35/EU, EN 61010; EN 60664-1	

Housing:

